# Specifications



**Photo is representative**





## Eaton 9PX3000IRTBP

Eaton 9PX UPS HotSwap IEC, 3000 VA, 3000 W, Input: C20, Outputs: (6) C13, (1) C19, Rack/tower, 3U

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton 9PX UPS |
| **CATALOG NUMBER** | 9PX3000IRTBP |
| **MODEL CODE** | Eaton 9PX 3000i RT3U HotSwap IEC |
| **UPC** | 743172081544 |
| **PRODUCT LENGTH/DEPTH** | 48.5 cm |
| **PRODUCT HEIGHT** | 13 cm |
| **PRODUCT WIDTH** | 44 cm |
| **PRODUCT WEIGHT** | 29.8 kg |
| **WARRANTY** | 3 year on electronics, 2 year on battery |
| **COMPLIANCES** | CE Marked<br>TUV<br>cULus Listed<br>CSA 22.2<br>FCC part 15 Class B<br>CISPR22 Class B |
| **CERTIFICATIONS** | EAC<br>CE<br>ENERGY STAR certified<br>IEC/EN 62040-1<br>UL 1778<br>IEC/EN 62040-2 |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **SPECIAL FEATURES** | • Double conversion topology<br>• Constantly monitors power conditions and regulates voltage and frequency<br>• First UPS in its class to provide Unity power factor (VA=W)<br>• Energy Star qualified, provides the highest efficiency level to reduce energy and cooling costs<br>• Internal bypass allows service continuity in case of UPS fault<br>• Next-generation graphical LCD display<br>• Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)<br>• Meter energy consumption (down to the managed outlet groups)<br>• Hot swappable batteries<br>• Advanced Battery Management (ABM) technology to increase battery lifetime<br>• Long backup time with up to 4 optional EBM |
| **TOPOLOGY** | Online/Double-conversion |
| **FORM FACTOR** | Rack/tower |
| **RACK SIZE** | 3U |
| **CONSTRUCTION TYPE** | 482.6 mm (19 inch) device |
| **COLOR** | Black/silver |
| **VA RATING** | 3000 VA |
| **WATTAGE** | 3000 W |
| **RACK MOUNTING KIT** | Yes |
| **PACKAGE CONTENTS** | • UPS<br>• Input cable<br>• Maintenance Bypass<br>• (2) IEC-IEC output cables<br>• USB cable<br>• Serial cable<br>• (2) brackets for 19’ mounting<br>• (2) Rack-mounting kit<br>• (2) Supports for tower mounting<br>• Cable locking system<br>• Safety instructions<br>• Quickstart guide |
| **INTERNAL BYPASS** | Yes |

## Resources

| | |
|---|---|
| **APPLICATION NOTES** | Eaton network closet solutions brochure<br><br>9PX5KP1 and 9PX6KP1 interconnect diagram<br><br>Application guide: Small data center power protection solutions<br><br>Eaton solutions for Cisco IDF/MDF closets |
| **BROCHURES** | Eaton 9PX 700-3000 VA UPS brochure<br><br>Eaton UPS and battery services - EN<br><br>Eaton UPS Services Quick Guide - EN |
| **COMPLIANCE INFORMATION** | EU declaration of conformity Eaton 9PX UPS |
| **MANUALS AND USER GUIDES** | Eaton 9PX 1-3 kVA UPS and 9PX EBM 48V and 72V - Installation and user manual<br><br>9PX 2-post rack kit user guide<br><br>9PX 700-3000 VA 2U UPS user guide<br><br>9PX UPS split-phase (6 kVA) guide<br><br>Eaton 9PX 1-3 kVA UPS - Quick Start Guide<br><br>9PX UPS (8-11 kVA) user guide<br><br>9PX UPS (5-6 kVA) user guide<br><br>9PX battery integration system user guide<br><br>9PX 3 kVA 3U UPS user guide<br><br>9PX supercharger 240 Vdc user guide<br><br>9PX UPS split-phase (8-10 kVA) user guide<br><br>9PX PPDM and transformers user guide<br><br>Eaton Bypass Power Module (BPM) user guide |
| **SPECIFICATIONS AND DATASHEETS** | 9PX technical specifications: 5 and 6 kVA<br><br>9PX UPS altitude de-ratings<br><br>9PX technical specifications: 8 and 11 kVA<br><br>Eaton 9PX UPS guide specification: 700-3000 VA |

| | |
|---|---|
| **HOT SWAP POWER** | Yes |
| **AUTO SHUTDOWN FUNCTION** | Yes |
| **PRIMARY FREQUENCY - MAX** | 70 Hz |
| **PRIMARY FREQUENCY - MIN** | 40 Hz |
| **INPUT CONNECTION** | C20 |
| **INPUT CORD LENGTH** | 1.8m |
| **INPUT NOMINAL VOLTAGE** | 230V default (200/208/220/230/240V) |
| **NOMINAL FREQUENCY** | 50/60 Hz |
| **INPUT FREQUENCY RANGE** | 40-70 Hz |
| **INPUT POWER FACTOR** | >.99 |
| **RECEPTACLE** | (6) C13, (1) C19 |
| **NUMBER OF OUTPUTS C13** | 6 |
| **NUMBER OF OUTPUTS C19** | 1 |
| **OUTPUT WAVEFORM** | Sine wave |
| **VOLTAGE** | 230V |
| **OUTPUT NOMINAL VOLTAGE** | 230V default (200/208/220/230/240V) |
| **FEED TYPE** | 1 |
| **VOLTAGE TYPE** | AC |
| **RUNTIME GRAPH** | View runtime graph |
| **BATTERY MANAGEMENT** | • ABM & Temperature compensated charging method (user selectable)<br>• Automatic battery test<br>• Deep discharge protection<br>• Automatic recognition of external battery units |
| **BATTERY REPLACEMENT** | Hot-swappable internal batteries and extended battery modules (EBMs) |
| **BATTERY RATING** | 12 V / 9 Ah |
| **BATTERY TYPE** | Sealed, lead-acid |
| **EXTENDED BATTERY CAPABILITY** | Yes |
| **RUNTIME AT HALF LOAD** | 9.5 min |
| **COMMUNICATION** | • USB port (HID compliant)<br>• Serial port (RS232)<br>• Mini terminal block for remote On/Off<br>• Mini-terminal block for remote power off<br>• Mini-terminal block for output relay |

| | |
|---|---|
| | 9PX 700-3000 VA UPS technical specification<br><br>Eaton Specification Sheet - 9PX3000IRTBP<br><br>9PX 3 kVA 3U UPS technical specification<br><br>9PX Split-phase technical specifications |
| **TECHNICAL DATA SHEETS** | Eaton 9PX 1000-3000W UPS - Datasheet |

| | |
|---|---|
| | • Dry contacts (3 outputs, 1 input, optocoupler, DB9) |
| **EXPANSION SLOTS** | One slot for optional communication card |
| **ETHERNET INTERFACE** | No |
| **INCLUDES NETWORK CARD** | No |
| **SOFTWARE COMPATIBILITY** | Eaton Intelligent Power Manager, Eaton Intelligent Power Protector |
| **USER INTERFACE** | Multilingual graphical LCD display |
| **TYPE OF INTERFACE** | Other |
| **POTENTIAL FREE SWITCH CONTACT** | Yes |
| **ALTITUDE** | 3000 m |
| **BTU RATING** | Online: 614 |
| **NOISE LEVEL** | <40 dB at 1 meter |
| **RELATIVE HUMIDITY** | 0-96% non-condensing |
| **TEMPERATURE RANGE** | 0° to 40°C (32° to 104°F) |
| **INPUT VOLTAGE - MAX** | 276 V |
| **INPUT VOLTAGE - MIN** | 100 V |
| **OUTPUT VOLTAGE - MAX** | 240 V |
| **OUTPUT VOLTAGE - MIN** | 200 V |
| **SECONDARY FREQUENCY - MAX** | 60 Hz |
| **SECONDARY FREQUENCY - MIN** | 50 Hz |
| **BATTERY QUANTITY** | 6 |
| **EFFICIENCY** | 94 |
| **EFFICIENCY (ECO-MODE)** | 98 |
| **INPUT VOLTAGE RANGE** | 176-276 V (100-276 V with derating) |
| **MAX NUMBER OF BATTERY PACKS** | 4 |
| **OUTPUT FREQUENCY** | 50/60 Hz |
| **OUTPUT POWER FACTOR** | 1 |
| **OUTPUT VOLTAGE RANGE** | 200/208/220/230/240 V +/- 1% |
| **PHASE (INPUT)** | 1 |
| **PHASE (OUTPUT)** | 1 |
| **RUNTIME AT FULL LOAD** | 3 min |
| **VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX** | 3 |
| **POWER CONSUMPTION** | 180 W |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc**
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.