Specifications



Photo is representative





Eaton 9PX8KIRTNBP

Eaton 9PX UPS HotSwap Netpack, 8 kVA, 7.2 kW, Input: Hardwired, Outputs: (4) C19, Hardwired, Rack/tower, 6U, Network card included

General specifications	
PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX8KIRTNBP
MODEL CODE	Eaton 9PX 8000i RT6U HotSwap Netpack
UPC	743172040268
PRODUCT LENGTH/DEPTH	70 cm
PRODUCT HEIGHT	26 cm
PRODUCT WIDTH	44 cm
PRODUCT WEIGHT	84 kg
COMPLIANCES	CE Marked TUV
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC

Powering Business Worldwide

Product specifications

SPECIAL FEATURES	• Double conversion topology • Constantly monitors power conditions and regulates voltage and frequency • Provides more real power (watts) to protect more equipment with a 0.9 power factor • Energy Star qualified, provides the highest efficiency level to reduce energy and cooling costs • Internal bypass allows service continuity in case of UPS fault • Next-generation graphical LCD display • Network card and rackmounting kit delivered as standard • Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat) • Meter energy consumption (at the UPS level) • Parallel operation using HotSync technology • Hot swappable batteries
TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack/tower
RACK SIZE	6U
CONSTRUCTION TYPE	482.6 mm (19 inch) device
COLOR	Black/silver
VA RATING	8 kVA
WATTAGE	7.2 kW
RACK MOUNTING KIT	Yes
PACKAGE CONTENTS	• Power Module • Extended battery module (EBM) • Maintenance Bypass • Network Management Card • (2) brackets for 19’ mounting • (2) Rack-mounting kit • USB cable • Serial cable • Battery cable with comms for automatic battery cabinet recognition • (2) Supports for tower mounting

Resources

APPLICATION NOTES	Eaton solutions for Cisco IDF/MDF closets
BROCHURES	Eaton UPS and battery services - EN Eaton UPS Services Quick Guide - EN Eaton 9PX UPS 5–22kVA - Brochure
COMPLIANCE INFORMATION	EU declaration of conformity Eaton 9PX UPS
MANUALS AND USER GUIDES	Eaton 9SX-9PX UPS - 8-11 kVA-EBM 240V - Installation and user manual Eaton Bypass Power Module (BPM) user guide
TECHNICAL DATA SHEETS	Eaton 9PX UPS - 5/6/8/11 kVA - Datasheet

	• Link plate • Safety instructions • Quickstart guide
INTERNAL BYPASS	Yes
HOT SWAP POWER	Yes
AUTO SHUTDOWN FUNCTION	Yes
PRIMARY FREQUENCY - MAX	70 Hz
PRIMARY FREQUENCY - MIN	40 Hz
INPUT CONNECTION	Hardwired/fixed connection
INPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240/250V)
NOMINAL FREQUENCY	50/60 Hz
INPUT FREQUENCY RANGE	40-70 Hz
INPUT POWER FACTOR	>.99
RECEPTACLE	(4) C19, Hardwired
NUMBER OF OUTPUTS C19	4
NUMBER OF OUTPUTS HARDWIRED	1
OUTPUT WAVEFORM	Sine wave
VOLTAGE	230V
OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240/250V)
FEED TYPE	1
VOLTAGE TYPE	AC
RUNTIME GRAPH	View runtime graph
BATTERY MANAGEMENT	• ABM & Temperature compensated charging method (user selectable) • Automatic battery test • Deep discharge protection • Automatic recognition of external battery units
BATTERY REPLACEMENT	Hot-swappable battery modules
BATTERY RATING	12 V / 9 Ah
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
RUNTIME AT HALF LOAD	16 min
COMMUNICATION	• USB port (HID compliant) • Serial port (RS232) • Mini terminal block for remote On/Off

	• Mini-terminal block for remote power off • Dry contacts (4 outputs, relay, DB9) • DB15 for parallel operation • Network card
EXPANSION SLOTS	One slot, network card included
ETHERNET INTERFACE	Yes
INCLUDES NETWORK CARD	Yes
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
USER INTERFACE	Multilingual graphical LCD display
TYPE OF INTERFACE	Other
POTENTIAL FREE SWITCH CONTACT	Yes
ALTITUDE	3000 m
BTU RATING	Online: 1472
NOISE LEVEL	<48 dB at 1 meter
RELATIVE HUMIDITY	0-95% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
PROTOCOL	SNMP
INTEGRATED FUNCTIONALITY	Network Mangement
INPUT VOLTAGE - MAX	276 V
INPUT VOLTAGE - MIN	100 V
OUTPUT VOLTAGE - MAX	250 V
OUTPUT VOLTAGE - MIN	200 V
SECONDARY FREQUENCY - MAX	60 Hz
SECONDARY FREQUENCY - MIN	50 Hz
BATTERY QUANTITY	20
EFFICIENCY	95
EFFICIENCY (ECO-MODE)	98
INPUT VOLTAGE RANGE	176-276 V (100-276 V with derating)
MAX NUMBER OF BATTERY PACKS	12 (supercharger required for more than 6 EBM)
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	0.9
OUTPUT VOLTAGE RANGE	200/208/220/230/240/250 V +/- 1%
PHASE (INPUT)	1
PHASE (OUTPUT)	1
RUNTIME AT FULL LOAD	5 min

VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	2
POWER CONSUMPTION	432 W

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.